




Fanvil H4/H4W Hotel Phone

Fanvil H4/H4W is a hotel IP phone with a cost-effective, multi-function, and elegant appearance. It is equipped with 5 programmable soft keys for the services hotline, meeting the application requirements of various hotel scenarios. H4W has built-in dual-band 2.4GHz & 5GHz Wi-Fi(Wi-Fi 6). In addition, it supports functions such as HD audio, 10/100Mbps network port, and integrated PoE, providing a high-quality user experience and reducing the cost of hotel deployment. It is more than a hotel phone and also can be applied in multiple scenarios, such as shopping malls, hospitals, and supermarkets.

Highlights

- ☑ Elegant and fashionable product appearance
- ☑ 5 programmable soft keys for service hotline
- ☑ Built-in dual-band 2.4GHz & 5GHz Wi-Fi(Wi-Fi 6)
- ☑ Unique customized faceplate
- ☑ Support audio codec G.722 and Opus, handling varieties of audio applications
- ☑ 10/100 Mbps port, integrated PoE



Generic

- 2 SIP Lines
- HD Voice
- PoE
- Built-in dual-band 2.4GHz & 5GHz Wi-Fi(Wi-Fi 6)
- Hand set / Hands-free mode
- Intelligent DSS Keys (speed dial key)
- Desktop Stand
- Optional External Power Supply(H4 sold separately)

Phone Functions

- Programmable DSS keys
- Action URL / Active URI
- Built-in dual-band 2.4GHz & 5GHz Wi-Fi(Wi-Fi 6)
 - 2.4GHz, 802.11 b/g/n
 - 5GHz, 802.11 a/n/ac/ax
- Web dial
- Dial plan
- SIP Hotspot
- Distinctive ring
- Multicast

Call Functions

- Call out / Answer
- Mute / Unmute
- Call Hold / Resume
- Speed Dial
- Hot Line

- Voice Message

Audio

- Wideband ADC/DAC 16KHz sampling
- HAC handset
- Narrowband codec: G.711A/U, G.729AB, G723.1, G726, iLBC
- Wideband codec: G.722, Opus
- Full-duplex hands-free speakerphone with AEC
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR) / Automatic Gain Control (AGC)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer
- DTMF: In-band, Out-of-Band – DTMF-Relay (RFC2833) / SIP INFO
- VQM voice quality monitoring

Network

- 10/100 Mbps Ethernet
- IP Mode:IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static / DHCP / PPPoE
- Wi-Fi Encryption:WPA /WPA2-PSK /802.X EAP
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN: 802.1P/Q
- QoS
- LLDP

- RTCP-XR (RFC3611), VQ-RTCPXR(RFC6035)

Protocols

- SIP v1 (RFC2543), v2 (RFC3261) over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- IPv6
- PPPoE
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

Deployment & Management

- Auto-provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- Web management portal
- Web-based packet dump
- Configuration export / import
- Firmware upgrade
- Syslog

Physical Specifications

- Keypad: 21 keys, including
 - 12 Standard Phone Digits keys
 - 5 DSS keys

- 3 Function keys (Up/Down/Mute)
- 1 hands-free key
- MSG indicator (with red color LED) x1
- Handset (RJ9) x1
- Standard RJ9 Handset Cord x1
- 1.5M CAT5 Ethernet Cable x1
- RJ9 Port x1: Handset x1
- RJ45 Port x1: Network x1
- Power: DC 5V 2A or PoE
- Power Consumption (PoE):
 - H4: 0.66~4.07 W
 - H4W: 0.94~5.79 W
- Power Consumption (Adapter):
 - H4: 0.85~5.5 W
 - H4W: 1.51~7.8 W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Installation:
 - Desktop
- Color: Black/White
- Qty/CTN: 10 pcs
- N.W/CTN: 7.85 kg
- G.W/CTN :8.80 kg
- Device Dimensions:
 - Desktop Stand (30°): 221x127.5x70.5 mm
- Gift Box Dimensions: 190x228x95 mm
- Outer CTN Dimensions: 495x476x210 mm (10 PCS)

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products. For more information, please visit: www.fanvil.com

