MAXHUB 01

V6 Classic Series Zoom Rooms Version

An all-in-one Zoom Rooms-enabled collaboration board to suit any meeting room.

From huddle rooms to large meeting rooms, MAXHUB IFP V6 Classic Zoom Rooms Version is pre-configured with Zoom Rooms to support Zoom Whiteboard with 10-point multi-touch functionality, annotation and Auto Framing.

The pluggable PC Module makes the IFP V6 Classic easy to upgrade while the color accuracy (smaller than 2 Delta E), 90% NTSC true color, 92° HFOV 48MP 4K UHD camera, 2.1 channel stereo sound and two 10W+20W seam speakers offer an immersive, true-to-life experience.





PC Module	MT61Z	MT61X
	CPU : Intel i5	CPU : Intel i7
Hardware	Memory: 16G	Memory: 16G
	Storage: 256G	Storage: 256G
OS	Windows 10 IOT	Windows 10 IOT
A 10 10	Zoom Rooms	Zoom Rooms
App	Preconfigured	Preconfigured



Professional 4K Display

High Color Accuracy, ΔE≤2 Wide Color Gamut, NTSC 90%



Touch Screen

20 Touch Points, Minimum Object Recognition - 2mm



Zoom Rooms

Pre-installed Zoom Rooms app based on windows



Bring Your Own Device

Access to MAXHUB V6 classic's camera / microphone / speaker from your laptop



Built-in Camera

48million pixels
Offer the best view in both dark/bright scene with WDR technology



Built-in Microphone

8 meters of voice pick-up



Built-in Speaker

2.1 Channel 2x 10W + 20W



Energy Saving

Energy Star 8.0 Certified* (touch display)

^{*}Must order with Zoom Rooms preconfigured PC module.

Display				
Model / Part No.	C5530	C6530	C7530	C8630
Diagonal Size(inch)	55	65	75	86
Backlight	Direct-lit LED	Direct-lit LED	Direct-lit LED	Direct-lit LED
Panel Technology	IPS	IPS	VA	VA
Aspect Ratio	16:9	16:9	16:9	16:9
Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
Refresh Rate	60Hz	60Hz	60Hz	60Hz
Response Time	8ms	8ms	8.5ms	8ms
Brightness(typ)	350cd/m ²	350cd/m ²	350cd/m ²	350cd/m ²
Contrast Ratio	1200:1	1200:1	5000:1	4000:1
Viewing Angle	178°/178°	178°/178°	178°/178°	178°/178°
Color Gamut(typ)	90% NTSC	90% NTSC	90% NTSC	90% NTSC
Display Orientation	Landscape	Landscape	Landscape	Landscape
Operating Hour	16/7	16/7	16/7	16/7

Dimension&Weight				
Product Dimensions(WxHxD)	1263 x 776 x 88 mm 49.72 x 30.55 x 3.46 inch	1488 x 903 x 88 mm 58.58 x 35.55 x 3.46 inch	1709 x 1026 x 87 mm 73.35 x 44.88 x 8.86 inch	1957.1 x 1160.1 x 100.2 mm 77.05 x 45.67 x 3.94 inch
Shipping Dimensions(WxHxD)	1392 x 847 x 220mm 54.8 x 33.35 x 8.66 inch	1638 x 1005 x 208mm 64.09 x 39.57 x 8.19 inch	1863 x 1140 x 225 mm 73.35 x 44.88 x 8.86 inch	2110 x 1283 x 225 mm 83.07 x 50.51 x 6.86 inch
Net Weight (kg /pounds)	26.25kg / 57.87 lbs	36.25kg / 79.92 lbs	48.3kg / 106.48 lbs	59.75kg / 131.73 lbs
Gross Weight (kg /pounds)	34.2kg / 75.40 lbs	46.75kg / 103.07 lbs	62.8kg / 138.45 lbs	77.00kg / 169.76 lbs
Wall Mount(VESA)	400 x 200mm / 15.75 x 7.78inch	600 x 400mm / 23.62 x 15.75inch	800 x 400mm / 31.50x15.75inch	800 x 600mm / 31.50 x 23.62inch
Screws For VESA	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch	M8 x 25mm / M8 x 0.99inch

POWER				
Power Supply	AC100-240V,50/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz	AC100-240V,50/60Hz
Max Power Consumption	300W	350W	400W	400W
Standby	≤0.5W	≤0.5W	≤0.5W	≤0.5W

Touch System	
Touch Sensor	IR Touch
Max Touch Points Supported	20
Accuracy	± 1 mm
Object Recognition Range	≥2mm
Glass	Zero parallax , 3mm Angi-glare, Antibacterial
Supported Operating System(Touch Return)	Windows10/Windows8/Windows7/WindowsXP/ Android/Linux/Mac OS X/Chrome OS

Camera/Audio/Microphone		
Built-in Camera	Yes, Single Camera, 48MP	
Camera Features	Auto Frame / Speaker Tracking	
Built-in Speakers	2.1 Channel , 2x10W+20W	
Microphone Array	8 x Far-field , beam-forming microphone - max 8m range	

Connectivity	
Input	HDMI IN x 1 , USB 2.0 x 1, USB 3.0 x 2, TOUCH 2.0 x 1 , USB Type-C x
Audio	Audio out x 1
Control	RS232 x 1
PC Module Slot	Yes, 3840 x 2160@60fps
PC Module (must o	der seperately) MT61Z / MT61X
Wifi Module	SI06

Environment	
Operating Temperature	0 °C ~40 °C
Storage Temperature	10%~90%RH
Operating Humidity	-20 °C ~60 °C
Storage Humidity	10%~90%RH

What's In The Box

Standard

Power Cord, 1 x Wifi Adapter, 2 x Passive Stylus, 1 x Wall Mount, 1 x Type-C Cable (1.8m | 70.9inch)

Optional (Mobile Stand)









MT61Z Specification

General Specifications Pluggable PC Module Device Type Operating System Win 10 IOT (64bit) CPU Intel Core i5 GPU Intel UHD Graphics (supports 4K@60Hz) RAM 16G , DDR4 Internal Storage 256G Touchscreen Compatibility Yes 2.0 TPM **Application** Zoom Rooms

Connectivity	
HDMI Out	1 (up to 4K@30fps)
USB 3.0	x3
USB 2.0	x1
RJ45 in	x1
Microphone in	x1

Power	
Power Requirements	18V DC
Power Consumption Maximum	≤ 106.5W
Power Consumption Standby	≤ 1.1W
ENVIRONMENTAL	

ENVIRONMENTAL	
Operating Temperature	-10° ~55°
Storage Temperature	-20° ~60°
Operating Humidity	10% - 90%RH
Storage Humidity	10% - 90%RH

Physical Specifications	
Product Dimensions (WxHxD)	202 x 133.5 x 30 mm
Package Dimensions (WxHxD)	314 x 256 x 70 mm
Net Weight	1.325 kg
Gross Weight	1.745 kg

Warranty	
Standard Warranty	3-year Warranty
Support	

MT61X Specification

General Specifications	
Device Type	Pluggable PC Module
Operating System	Win 10 IOT (64bit)
CPU	Intel Core i7
GPU	Intel UHD Graphics (supports 4K@60Hz)
RAM	16G , DDR4
Internal Storage	256G
Touchscreen Compatibility	Yes
TPM	2.0
Application	Zoom Rooms

Connectivity	
HDMI Out	1 (up to 4K@30fps)
USB 3.0	x3
USB 2.0	x1
RJ45 in	x1
Microphone in	x1

Power	
Power Requirements	18V DC
Power Consumption Maximum	≤ 106.5W
Power Consumption Standby	≤ 1.1W

ENVIRONMENTAL	
Operating Temperature	-10° ~55°
Storage Temperature	-20° ~60°
Operating Humidity	10% - 90%RH
Storage Humidity	10% - 90%RH

Physical Specifications	
Product Dimensions (WxHxD)	202 x 133.5 x 30 mm
Package Dimensions (WxHxD)	314 x 256 x 70 mm
Net Weight	1.325 kg
Gross Weight	1.745 kg

Warranty	
Standard Warranty	3-year Warranty

A		
Support		
Juppoit		

For all MAXHUB Products , visit https://www.maxhub.com/en/service







For all MAXHUB Products , visit https://www.maxhub.com/en/service